

List of Registered Sewage Tanks
Effective Date: June 2017

Manufacturer	Model Number	Tank Size (gallons)	Number of Compartments	Usage	Approved / Renewal	Limitations
Premier Plastics Inc. 8328 River Way Delta B.C. Canada V4G 1C4 1-800-661-4473 604-952-6686 604-952-6696 (fax) www.premierplastics.com office@premierplastics.com Tank Material: Polyethylene	STSU1500EH (PCU1500D)	1500	Two	Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank	4-27-2010 / 12-31-2018	Anti-buoyancy measures required if water table submerges tank bottom >24". 4' maximum depth of burial.
	STSU1000EH (PCU1000D)	1000	One / Two	Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank	8-19-2010 / 12-31-2018	Anti-Buoyancy measures required if water table above tank bottom. 4' maximum depth of burial.
	STSU1300 (PCU1300D)	1300	One / Two	Septic Tank, Grease Interceptor, Pump Tank, Trash Tank, Holding Tank	8-19-2010 / 12-31-2018	Anti-Buoyancy measures required if water table above tank bottom. 4' maximum depth of burial.
	FLTU155	90 (max dose)	One	Flout Dosing Tank	10-1-2013 / 12-31-2018	Must be preceded by 2-compartment septic tank with effluent filter. 4' maximum depth of burial. Anti-buoyancy measures may be required for <4' cover and high water table.
	FLTU210	138 (max dose)	One	Flout Dosing Tank	10-1-2013 / 12-31-2018	Must be preceded by 2-compartment septic tank with effluent filter. 4' maximum depth of burial. Anti-buoyancy measures may be required for <4' cover and high water table.

List of Registered Sewage Tanks

Effective Date: June 2017

Manufacturer	Model Number	Tank Size (gallons)	Number of Compartments	Usage	Approved / Renewal	Limitations
Premier Plastics Inc. (continued)	FLTU275	192 (max dose)	One	Flout Dosing Tank	10-1-2013 / 12-31-2018	Must be preceded by 2-compartment septic tank with effluent filter. 4' maximum depth of burial. Anti-buoyancy measures may be required for <4' cover and high water table.
	FLTU455	330 (max dose)	One	Flout Dosing Tank	10-1-2013 / 12-31-2018	Must be preceded by 2-compartment septic tank with effluent filter. 4' maximum depth of burial. Anti-buoyancy measures may be required for <4' cover and high water table.
	PCU575 Fat Albert	575	One	Pump Tank	3-19-2014 / 12-31-2018	Anti-Buoyancy measures required if evidence of a water table is present and soil cover is less than 3 feet. 3' maximum burial depth
	PCU575 EH Fat Albert	575	One	Pump Tank	3-19-2014 / 12-31-2018	Anti-Buoyancy measures required if evidence of a water table is present and soil cover is less than 3 feet. 5' maximum burial depth